


Specification ST_v21

YARDMASTER® STIRRER

- With a developing need to keep a good solid / liquid mix, the Yardmaster range of stirrers have become a key element of many effluent systems
- Using a 4-pole motor, the Yardmaster stirrer runs through a reduction gearbox to do approximately 100rpm at the propeller
- Available in 3 motor options, there is a stirrer to suit most applications
- Mounting the stirrer can be done in various ways. Where your pontoon provides sufficient buoyancy and size, it can be fitted on a single pontoon with your pump
- Alternatively you can have a separate pontoon for a pump and stirrer. Your stirrer can also be frame mounted, with longer shaft stirrers available for this purpose
- Designed and manufactured in New Zealand for New Zealand conditions

Product Codes (Standard Series)

DESCRIPTION	CODE
EFFLUENT STIRRER	
Yardmaster stirrer complete; RHST2, 2hp	RHST2
Yardmaster stirrer complete; RHST4, 5hp	RHST4
Yardmaster stirrer complete; RHST6, 10hp	RHST6



Applications & Case Studies



CS_TRO01
Pond installation, effluent pump, stirrer and stabilised long arm

CS_TMC01
Long shaft stirrer and extender pump on fixed frame over pit

CS_HED01
Pit Installation, effluent pump and stirrer and short stabilised arm

CS_BEN01
Stirrer in pit, directly off feed pad transferring to separator

Specifications are subject to change without notice

